

KPC149E

H.R. IR CAMERA



● FEATURES

- (1) Cable management to prevent intentional cable damaging
- (2) High resolution of 520 TV Lines
- (3) High sensitivity in the dark environment, 0.1 Lux / F2.0, 0 Lux (IR ON)
- (4) Day and night features for 24-hour surveillance
- (5) IR distance: up to 40 meters with 56 IR LEDs
- (6) IP67, suitable for outdoor use

● SPECIFICATIONS*

Model	KPC149E
Pick up Element	1/3" HR color CCD image sensor
Number of Pixel	768(H) x 494(V) <NTSC> / 752(H) x 582(V) <PAL>
Resolution	520 TV lines
Minimum illumination	0.1 Lux / F2.0, 0 Lux (IR ON)
IR LED	56 units
IR Effective Range	Up to 40 meters
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f6.0mm / F2.0
Lens Angle	54°
White Balance	ATW
AGC	Auto
IRIS Mode	AES
IP Rating	IP67
Video Output	1.0Vp-p composite, 75Ω
Operating Temperature	0°C~40°C
Power Source (±10%)	DC12V / 1A
Current Consumption (±10%)	70mA (IR OFF), 590mA (IR ON)
Dimensions (mm)**	115.6(Ø) × 216.4(H)

* The specifications are subject to change without notice.

* Dimensional Tolerance: ± 5mm